

DT98A629

PRESSURE SENSORS • CONNECTION G1" OUTER

pressure transmitter, Ø26mm 113long, 0-0.25bar, 8-32V DC, G1 inch A, -40-85°C, 4-20mA, Valve connector type A 2pin, IP65, V4A, Front-flush membrane



MECHANICAL FEATURES

Ambient temperature	-40 °C ... 85 °C
Bursting pressure	1.5 bar
Degree of protection (IP)	IP65
Design	Cylinder plain
Explosion-proof	-
For liquid media	+
For pasty media	+
Front-flush membrane	+
Housing material	Stainless steel 1.4404
Max. operating pressure	1000 hPa
Max. operating pressure	1 bar
Medium temperature	-40 °C ... 125 °C
Nominal pressure	0.25 bar
Pressure transmitter	+
Sensing element material	Stainless steel 1.4435
Sensor diameter	26.5 mm
Sensor length	113 mm
Thread length	20.5 mm
Thread pitch	2.31 mm
Type of pressure connection	G1 inch A
With hand operation	-

ELECTRICAL FEATURES

Measurement method	Relative
Measuring range pressure	0 bar ... 0.25 bar
Number of pins	2
Operating voltage	8 V ... 32 V
Relative measurement accuracy	0.5 %
Response time	10 ms
Reverse polarity protection	+
Short-circuit protection	+
Suitable as 2-point control	-
Suitable as limiter	-

ELECTRICAL FEATURES

Suitable as monitor	-
Temperature drift	1.5 %
Type of analog output	4 mA ... 20 mA
Type of electrical connection	Valve connector type A
Voltage type	DC

OTHER FEATURES

For hydraulic applications	+
Measuring display	Relative

Other

Packaging dimensions	138.0mm x 95.0mm x 210mm
Shipping weight	0.57kg
Tariff code	90262020

Classification

ipf product group	700
eClass 8.0	27371814
eClass 9.0	27371814
eClass 9.1	27371814
ETIM-5.0	EC000243
ETIM-6.0	EC000243
ETIM-7.0	EC000243

Connection

Dimensional drawing

Installation



Mounting / installation may only be carried out by a qualified electrician!

Disposal



Safety warnings

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information. Never use these devices in applications where the safety of a person depends on their functionality. LED lighting systems can generate intensive UV radiation, which can damage your eyes in case of improper use. The manufacturer cannot be held responsible for damages that result from improper use or connection.