

MZ15A315

Magnetic field sensors • Sensors for trapezoidal groove

Magnetic Sensor, Cylinder, Trapezoidal Groove, 14x20x14mm, 10–30 V DC, 1x PNP NO, 3-pin M8 connector, IP67, zinc diecast, LED, 2.5 mT, top-mounted installation, short travel path, sensor surface centered on the device

- / Große_Schaltgenauigkeit_bei_kleiner_Hysteresis
- / Hohe_Schaltfrequenz



Einfach_von_oben_montierbar

Unabhängig_vom_Zylinderhersteller_einsetzbar

For many applications in automation technology, it is necessary to perform recognition of the motion of pneumatic and hydraulic cylinders and to precisely measure the position of the piston. Magnetic cylinder sensors are used for this purpose; they are mounted on the cylinders either directly from the outside or using adapters.

Electrical features

Number of switching outputs	1
Display	LED display
Type of switching function	Normally open contact (NO)
Type of electrical connection	Connector M8
Type of switching output	PNP
Rated switching current	150 mA
Absolute hysteresis	1 mm
No-load current	15 mA
Magnetic sensitivity	2.5 mT
Number of pins	3
Switching frequency	1000 Hz
Sensor surface (active)	Middle area
Voltage drop	2 V
Absolute repeat accuracy	0.1 mm
Operating voltage (DC)	10 - 30 V
Electrical connection	M8 3-pin plug connector
ardTEEL_Schutzfunktionen	Short circuit protection Reverse polarity protection

Mechanical features

Design	Cuboid
Width	13.5 mm
Height	13.5 mm
Sensor surface position	Center of the device
Length	20 mm
Mounting access, cylinder groove	From the top
Degree of protection (IP)	IP67
Housing material	Zinc die-cast
Ambient temperature	-25 - 75 °C
dimensions	20x13.5x13.5mm
ardTEME_Umgebungsbestaendigkeiten	Öle Kühlschmiermittel starke Erschütterungen/ Bewegungen

Other features

Features	short crossing distance
Harsh environmental conditions	Yes


Classification

ETIM 8


More

IPF Product Group	223 pneumatic cylinder sensors (diverse)
packaging dimensions	120 x 100 x 17 mm
gross weight	14 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection



Dimensional drawing



Extract accessories program

VK200271



Connection cable, 2m, M8 socket 3-pin angular, free cable end, 3x0.34mm², PUR (polyurethane), Ø4.3mm, -30-90°C, IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free

VK500271



Connection cable, 5m, M8 socket 3-pin angular, free cable end 3-pin, 3x0.34mm², PUR (polyurethane), Ø4.3mm, -30-90°C, IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free

NG530002



DC power supply, single-phase, 99x114x22mm, 24V, 0.1A, Number of relay outputs 2, 100-264V AC 50Hz, 100-264V AC 60Hz, Screw connection, IP20, Plastic, Stabilized, Output voltage, pulsed

VK030F72



Connection cable, 0.3m, M8 socket 3-pin angular, M8 connector 3-pin straight, 3x0.34mm², PUR (polyurethane), IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free

VK060F72



Connection cable, 0.6m, M8 socket 3-pin angular, M8 connector 3-pin straight, 3x0.34mm², PUR (polyurethane), IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free

VY000004



DC power supply, sensor tester, 120x26x72mm, 18V, 0.04A, Spring clamp connection 4pin, IP20, Plastic

VK003070



Cable socket, Angular, Suitable for self-assembly, Soldering connection, Ø3.5-5mm, 4A, 60V, -40-85°C, M8 Female (socket) 3pin, IP67, Brass

VK003074



Cable socket, Straight, Suitable for self-assembly, Soldering connection, Ø3.5-5mm, 4A, 60V, -40-85°C, M8 Female (socket) 3pin, IP67, Brass

VK030F82



Connection cable, 0.3m, M8 socket 3-pin angular, M12 connector 3-pin straight, 3x0.34mm², PUR (polyurethane), IP67, LED, suitable for trailing chain and torsion resistant, oils and cooling lubricants, welding area, silicone-free

You can find further accessories on our homepage

**Installation**

Mounting / installation may only be carried out by a qualified electrician!

**Disposal**

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

- / Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.
- / Never use these devices in applications where the safety of a person depends on their functionality.