

## OE110100

### Optical sensors • Through-beam sensors receivers

Sensor Optical, through-beam sensor receiver, 58x12x8mm, Sn: 2.5m, 10-30V diagnostic coverage, PNP NO, cable tail 3-pin 2m PVC, IP65, anodized/anodized aluminum + plastic PC, infrared light



Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

#### Electrical features

Response/decay time	2.5ms
Display	LED display
Type of switching function	Normally open contact (NO)
Type of electrical connection	Cable
Type of switching output	PNP
Rated switching current	100mA
Short-circuit protection	Yes
No-load current	24mA
No-load current, receiver	24mA
Number of pins	3
Switching distance	0 - 2500mm
Switching frequency	200Hz
Voltage drop	2V
Scanning function	Dark switching
Reverse polarity protection	Yes
Decay time	2.5ms
Operating voltage (DC)	10 - 30V

**Mechanical features**

Conductor cross-section	0.25mm <sup>2</sup>
Design	Cuboid
Width	8mm
Height	58mm
Cable length	2m
Length	12mm
Surface	teflon coated
Degree of protection (IP)	IP65
Active area material of sensor	Plastic (PC)
Housing material	Aluminum
Material of cable sheath	Plastic (PVC)
Ambient temperature	-25 - 65°C

**Optical features**

Light source	Infrared light
Light beam form	Point
Wavelength of the sensor	880nm

**Other features**

Scope of delivery	Receiver
Version	Through-beam sensor receiver


**Classification**

ETIM 8	EC002716 Through-beam photoelectric sensor
--------	--

**More**

IPF Product Group	100 optical sensors
packaging dimensions	123 x 77 x 25 mm
gross weight	50 g
Customs tariff number	85365019
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

**Connection**



**Installation**



Mounting / installation may only be carried out by a qualified electrician!

**Disposal**



**Safety warnings**

Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

Never use these devices in applications where the safety of a person depends on their functionality.

For suitable connection and mounting accessories, please refer to our website [www.ipf-electronic.com](http://www.ipf-electronic.com).

**Dimensional drawing**

