


OT059175

Optical sensors • Diffuse reflection sensors with intensity differentiation

Optical sensor, diffuse reflection sensor, M5x0.5 36lang, Sn: 20, 10-30V DC, 1x PNP NO, IO-Link, M8 cable connector 3-pin 0.3m PUR (polyurethane), IP67, V2A+PMMA, 1kHz, red light unpolarized, dot

including Nut, Toothed washer



Optical sensors work contactless. They detect objects, regardless of their properties (e.g. shape, color, surface structure, material). The basic mode of operation is based on the transmitter and receiver of light. There are three different versions: 1. the through-beam sensor consists of two separate devices, a transmitter and a receiver, which are aligned with each other. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. in the reflex light barrier, the transmitter and receiver are located in one device. The transmitted light beam is reflected onto the receiver by a reflector to be mounted opposite. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. the diffuse reflection sensor has a transmitter and receiver in one device. The transmitted light beam is reflected by the object to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Response/decay time	0.5 ms
Number of switching outputs	1
Display	LED display
Type of switching function	Normally open contact (NO)
Type of electrical connection	Cable connector M8
Type of switching output	PNP
Rated switching current	100 mA
Short-circuit protection	Yes
No-load current	12 mA
Number of pins	3
Residual ripple	10 %
Switching distance	20 mm
Switching frequency	1000 Hz
Protection class	III
Voltage drop	2 V
Scanning function	Light switching
Reverse polarity protection	Yes
Decay time	0.5 ms
Supported communication interface	IO-Link
Operating voltage (DC)	10 - 30 V

Mechanical features

Number of cores	3
Conductor cross-section	0.14 mm ²
Design	Cylinder, screw-thread
Thread length	30 mm
Thread pitch	0.5 mm
Cable length	0.3 m
Length	36 mm
Maximum tightening torque	1 Nm
Degree of protection (IP)	IP67
Active area material of sensor	Plastic (PMMA)
Housing material	Stainless steel (V2A)
Material of cable sheath	Plastic (PUR)
Thread dimension	M5
Ambient temperature	-25 - 65 °C

Optical features

Light source	Polarity free red light
Light exit	axial
Light beam form	Point
Wavelength of the sensor	630 nm

Other features

IO-Link version	V1.0.1
Feeding technology	Yes
Reference medium / object	Material with 90% reflectivity


Classification

ETIM 8	EC001821 Light sensor energetic
--------	---------------------------------


More

IPF Product Group	100 optical sensors
packaging dimensions	210 x 180 x 10 mm
gross weight	22 g
Customs tariff number	85365019
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection



Dimensional drawing



Extract accessories program

AV000142



accessories cable socket,
Mounting clip, 8.5mm, PPO,
Packaging unit 5, Accessories for
Cable socket/connector M8

AY000141



Plastic sheath, Ø17mm, Inner
diameter 10mm, -40-250°C, Glass
fiber with silicone rubber, Short-
term resistance to weld spatter
1200°C, Tensile strength 400N,
Flexible, Flame retardant, yard
good

VK200271



Connection cable, 2m, M8 Female
(socket) 3pin Angular, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, -30-
90°C, IP67, With LED display,
Suitable for trailing chain and
torsion resistant, Oil and cooling
lubricants, Welding area, Silico...

VK500271



Connection cable, 5m, M8 Female
(socket) 3pin Angular, Free
conductor end 3pin, 3x0.34mm²,
PUR (Polyurethane), Ø4.3mm, -30-
90°C, IP67, With LED display,
Suitable for trailing chain and
torsion resistant, Oil and cooling
lubricants, Welding area, S...

VK200071



Connection cable, 2m, M8 Female
(socket) 3pin Angular, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 60V, -
40-90°C, IP67, TPU, Suitable for
trailing chain and torsion resistant,
Oil and cooling lubricants, Welding
area, Silicone-free

VK200075



Connection cable, 2m, M8 female
(socket) 3pin Straight, free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 60V, -
30-90°C, IP67, suitable for trailing
chain and torsion resistant, oil and
cooling lubricants, welding area,
Silicone-free

VK030F82



Connection cable, 0.3m, M8
socket 3-pin angular, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), IP67,
LED, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK060F82



Connection cable, 0.6m, M8
socket 3-pin angular, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), IP67,
LED, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

AY000115



accessories sensor, Fixture kit,
Metal, ball joint

You can find further accessories on our homepage



Installation

Mounting / installation may only be carried
out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

/ Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

/ Never use these devices in applications where the safety of a person depends on their functionality.

/ Any software, drivers or IODD files that may be required to operate your device can be downloaded free of charge from our homepage: www.ipf-electronic.com