

PS991322

Laser sensors • Through-beam sensors transmitters

sensor laser, Through-beam sensor transmitter, 64x14x12mm, Sn: 150m, 12-32V DC, Connector M8 3pin, IP67, Brass Nickel-plated, Laser diode, red light



Optical sensors function contactlessly. They detect objects independent of their characteristics (e.g., shape, color, surface structure, material). The basic operating principle is based on the transmission and reception of light. There are three different versions: 1. The through-beam sensor consists of two separate devices, a transmitter and a receiver that are aligned with one another. If the light beam between the two devices is interrupted, the switching output integrated in the receiver changes its status. 2. With the retro-reflective sensor, the transmitter and receiver are located in one device. The emitted light beam is reflected back to the receiver by a reflector that is to be mounted opposite the device. As soon as the light beam is interrupted, the switching output integrated in the device changes its status. 3. With the diffuse reflection sensor, the transmitter and receiver are in one device. The emitted light beam is reflected by the object that is to be detected. As soon as the receiver detects the reflected light, the switching output integrated in the device changes its status.

Electrical features

Type of electrical connection	Connector M8
Setting procedure	other
Laser power	1 mW
No-load current	110 mA
Number of pins	3
Switching distance	0 - 150000 mm
Switching frequency	1000 Hz
Absolute repeat accuracy	0.01 mm
Operating voltage (DC)	12 - 32 V

Mechanical features

Design	Cuboid
Width	12 mm
Height	64 mm
Storage temperature	-20 - 85 °C
Length	14 mm
Surface	nickel-plated
Degree of protection (IP)	IP67
Housing material	Brass
Ambient temperature	-20 - 50 °C

Optical features

Filter	Interference filter
Laser class	Class 1
Light source	Laser diode, red light
Light beam form	Line
Wavelength of the sensor	670 nm


Classification

ETIM 8	EC002716 Through-beam photoelectric sensor
--------	--

More

IPF Product Group	705 special devices (SI)
packaging dimensions	123 x 77 x 25 mm
gross weight	80 g
Customs tariff number	85365019
WEEE number	40951076
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection



Extract accessories program

VK000036



Adaption, M8 Female (socket)
3pin Straight, M12 Male
(connector) 3pin Straight, 24V, -
25-85°C, IP67, Oil and cooling
lubricants, Welding area

You can find further accessories on our homepage



Installation

Mounting / installation may only be carried out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

- /** Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.
- /** Never use these devices in applications where the safety of a person depends on their functionality.