

UT30E278

Ultrasonic sensors • Distance measurement

sensor ultrasonic, diffuse-reflection sensor, M30x1.5 104long, Sn: 150-1500, 19-29V DC, 4-20mA, Connector M12 5pin, IP67, V4A, ultrasonic cone Axial



Ultrasonic sensors are non-contact and wear-free position switches which can also be used under rough environmental conditions. A key advantage of these devices lies in the fact that the material and the surface characteristics of the objects to be detected can be almost anything. Solids, liquids, grainy materials and powdery materials can be identified without the shape or the color of the object having any influence to the measured result. In addition, the ability to detect transparent materials such as films and fluids is of particular importance. The shape and color of the objects do not influence the result of the detection. The capability to detect transparent films or liquids is also of special importance. Ultrasonic sensors are used for distance measurement (e.g. detection of diameters, loop control), for fill level detection (e.g. silo detection), for positioning and presence detection (e.g. glass pane positioning, film tear check, glass bottle detection)

Electrical features

Response/decay time	120 ms
Resolution	0.5 mm
Type of analog output	4 - 20mA
Type of electrical connection	Connector M12
Short-circuit protection	Yes
Load resistance (current output)	0.5 kOhm
No-load current	25 mA
Number of pins	5
Relative linearity deviation	0.5 %
Relative repeat accuracy	0.2 %
Sound outlet	axial
Protection class	III
Temperature drift over entire measuring range	0.02 %
Carrier frequency	120 kHz
Reverse polarity protection	Yes
Operating voltage (DC)	19,2 - 28,8 V
Measuring range	150 - 1500 mm

Mechanical features

Design	Cylinder, screw-thread
Thread length	52.5 mm
Thread pitch	1.5 mm
Length	104 mm
Degree of protection (IP)	IP67
Housing material	Stainless steel 1.4404
Diameter detection	Yes
Thread dimension	M30
Ambient temperature	-20 - 70 °C

Optical features

Angle of beam spread	40 °
----------------------	------

Other features

Operating frequency	120 kHz
ardTE00_Anwendungen	Niveauabfrage


Classification

ETIM 8	EC001846 Ultrasonic distance sensor
--------	-------------------------------------



More

IPF Product Group	259 ultrasonic sensors (analog)
packaging dimensions	275 x 90 x 90 mm
gross weight	263 g
Customs tariff number	85365019
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

Connection




Dimensional drawing




Extract accessories program

VK205621




VK205625



AY000162



AY000159



AY000015



You can find further accessories on our homepage



Installation

Mounting / installation may only be carried out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3 ElektroG: 40951076

Safety warnings

/ Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

/ Never use these devices in applications where the safety of a person depends on their functionality.