

VK207B41

Connection technology • Cable sockets / connectors pre-assembled on one side

Connection cable, 2m, M9 connector 8-pin angular, free cable end, 8x0.14mm², PUR (polyurethane), 125V, IP67, shielded, oils and cooling lubricants, welding area



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

Electrical features

Type of plug-in contact, A connection	Male (connector)
Type of A electrical connection	M9
Type of B electrical connection	Free conductor end
Flow resistance	3 mOhm
Number of pins of A connection	8
Ampacity	1 A
Operating voltage (AC 50Hz)	125 V
Operating voltage (DC)	125 V
Shielded	Yes

Mechanical features

Number of cores	8
Conductor cross-section	0.14 mm ²
Cable length	2 m
Cable infeed of A connection	angular
Degree of protection (IP)	IP67
Material of cable sheath	Plastic (PUR)
Ambient temperature	-25 - 70 °C

Other features

Flame retardant	No
Welding area	Yes
Oil and cooling lubricants	Yes

Classification


ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

More

IPF Product Group	856 cable socket / cable connector (diverse)
packaging dimensions	220 x 160 mm
gross weight	110 g
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes


Connection

connector



- 1** white
- 2** brown
- 3** green
- 4** yellow
- 5** gray
- 6** black or pink
- 7** blue
- 8** red

Dimensional drawing



Extract accessories program

AY000141



Plastic sheath, Ø17mm, Inner diameter 10mm, -40-250°C, Glass fiber with silicone rubber, Short-term resistance to weld spatter 1200°C, Tensile strength 400N, Flexible, Flame retardant, yard good

AV98F001



AV98F002



Tool, wrench insert for torque wrench, SW13

AV000140



You can find further accessories on our homepage



Installation

Mounting / installation may only be carried out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

- / Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.
- / Never use these devices in applications where the safety of a person depends on their functionality.