

## VK500361

### Connection technology • Cable sockets / connectors pre-assembled on one side

Connection cable, 5m, M5 Female (socket) 4pin Angular, Free conductor end 4pin, 4x0.14mm<sup>2</sup>, PUR (Polyurethane), Ø3.5mm, 125V, IP67, Oil and cooling lubricants



ipf cable sockets are used primarily for establishing the electrical connection of sensors. Their features are characterized by rugged design, the highest protection classes (IP67 | IP68 | IP69K) and, if desired, with 360° shielding. With the features: bus-ready, suitable for use with drag chains and robots, resistance to oil and chemicals, resistance to welding sparks, their resistance to cleaning agents or high-pressure and steam-jet cleaning, the expanded temperature range of up to +230°C, the rapid interconnection technology and special data transmission properties, the cable sockets meet all requirements in automation technology.

#### Electrical features

Type of plug-in contact, A connection	Female (socket)
Type of A electrical connection	M5
Type of B electrical connection	Free conductor end
Number of pins of A connection	4
Number of pins of B connection	4
Operating voltage (AC 50Hz)	125 V
Operating voltage (DC)	125 V

#### Mechanical features

Number of cores	4
Conductor cross-section	0.14 mm <sup>2</sup>
Cable length	5 m
Cable infeed of A connection	angular
Degree of protection (IP)	IP67
Material of cable sheath	Plastic (PUR)
Perm. ambient temperature of cable, fixed cable	-25 - 80 °C
Suitable for trailing chain	Yes
Material of the screw fitting	Brass
Line diameter	3.5 mm

#### Other features

Flame retardant	No
Halogen-free	Yes
Oil and cooling lubricants	Yes


**Classification**

ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--

**More**

IPF Product Group	856 cable socket / cable connector (diverse)
packaging dimensions	150 x 150 x 20 mm
gross weight	80 g
Customs tariff number	85444290
WEEE number	40951076
OzDS-compliant	Yes
POP-compliant	Yes
Reach-compliant	Yes
RoHS-compliant	Yes

**Connection**



- 1** brown
- 2** white
- 3** blue
- 4** black

**Extract accessories program**

**AV98F001**



**AV98F002**



Tool, wrench insert for torque wrench, SW13

**AY000141**



Plastic sheath, Ø17mm, Inner diameter 10mm, -40-250°C, Glass fiber with silicone rubber, Short-term resistance to weld spatter 1200°C, Tensile strength 400N, Flexible, Flame retardant, yard good

**AV000116**



Labeling material, Label sleeve, 30mm long, Cable diameter 3.7-6.2mm, Plastic, Transparent

**AV000140**



You can find further accessories on our homepage

**Installation**

Mounting / installation may only be carried out by a qualified electrician!

**Disposal**

WEEE number according to § 6 para. 3  
ElektroG: 40951076

**Safety warnings**

- / Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.
- / Never use these devices in applications where the safety of a person depends on their functionality.