

VKABHW2W

Connection technology • Cable sockets / connectors pre-assembled on two sides

Connection cable, 12m, M12 socket 3-pin straight, M12 connector 3-pin straight, 3x0.22mm², PTFE with stainl. steel braiding, -55-180°C



This connection cable has pre-wired connections on both sides. It can be used to cost-effectively integrate end devices with a plug connection via a distribution terminal or a logic module.

Electrical features

Type of plug-in contact, A connection	Female (socket)
Type of plug-in contact, B connection	Male (connector)
Type of A electrical connection	M12
Type of B electrical connection	M12
Number of pins of A connection	3
Number of pins of B connection	3

Mechanical features

Number of cores	3
Wire assembly	28 x 0.1mm
Conductor cross-section	0.22 mm ²
Cable length	12 m
Cable infeed of A connection	straight
Cable infeed of B connection	straight
Coding of connection A	A
Coding of connection B	A
Maximum tightening torque of connection A	1 Nm
Maximum tightening torque of connection B	1 Nm
Material of cable sheath	PTFE with stainl. steel mesh
Perm. ambient temperature of cable, fixed cable	-55 - 180 °C
Line diameter	3.7 mm

Other features

Flame retardant	No
-----------------	----


Classification

ETIM 8	EC001855 Assembled sensor-actuator cable
--------	--


More

IPF Product Group	853 cable sockets / connectors (high temperature)
packaging dimensions	300 x 200 x 20 mm
gross weight	387 g
Customs tariff number	85444290
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection



Dimensional drawing



Extract accessories program

AV000141



accessories cable socket,
Mounting clip, 13.5mm, PPO,
Packaging unit 5, Accessories for
Cable socket/connector M12

AV98F001



AV98F002



Tool, wrench insert for torque
wrench, SW13

AY000141



Plastic sheath, Ø17mm, Inner
diameter 10mm, -40-250°C, Glass
fiber with silicone rubber, Short-
term resistance to weld spatter
1200°C, Tensile strength 400N,
Flexible, Flame retardant, yard
good

VK000037



Adaption, M12 Female (socket)
3pin Straight, M8 Male
(connector) 3pin Straight, 24V, -
25-85°C, IP67, Oil and cooling
lubricants, Welding area

AV000140



You can find further accessories on our homepage



Installation

Mounting / installation may only be carried
out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

/ Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

/ Never use these devices in applications where the safety of a person depends on their functionality.