

VY03E115

Connection technology • Timer stages

time stage, Turn-off delay, 0.03s, 10-35V DC, 1x NO, M12 3pin 0.3m, IP67, Plastic



Our multi-function time relays / pulse stretchers can be considered as real alternatives when it comes to solutions for minor set control technology problems. The input signals, for example, can be switch-on or off delayed after a preset time. In order to be able to reduce the storage, multi-function relays can be used that provide, in addition to the already mentioned functions, operating modes like time-programming, pulse-forming or clocking. Besides, there is also star / delta change-over for load-contactors integrated in the motor start control. Reversing the switching logic or the polarity is possible with our fast signal inverters / impulse stretchers. These are characterized by extremely short response times and high switching frequencies. As an input circuit for a PLC these devices are perfect to record short signal or level changes.

Electrical features

Number of outputs, delayed, normally open contact	1
Number of switching outputs	1
Number of time ranges	1
Display	LED display
Type of signal processing	Turn-off delay
Type of input signal	PNP
Type of plug-in contact, A connection	Female (socket)
Type of plug-in contact, B connection	Male (connector)
Type of switching function	Normally open contact (NO)
Type of switching output	PNP
Type of signal input A	PNP
Type of A electrical connection	M12
Type of B electrical connection	M12
Rated switching current	150 mA
Setting procedure	Manual adjustment
Pulse stretching	30 ms
Short-circuit protection	Yes
No-load current	20 mA
Number of pins of A connection	3
Number of pins of B connection	4
Switching voltage	35 V
Time range	0,03 s
Operating voltage (DC)	10 - 35 V

Mechanical features

Cable length	0.3 m
Cable infeed of A connection	straight
Cable infeed of B connection	straight
Mounting method	Direct mounting
Degree of protection (IP)	IP67
Housing material	Plastic
Ambient temperature	-25 - 70 °C


Classification

ETIM 8	EC001439 Time relay
--------	---------------------


More

IPF Product Group	800 miscellaneous
packaging dimensions	123 x 77 x 25 mm
gross weight	38 g
Customs tariff number	85365005
WEEE number	40951076
Reach-compliant	Yes
RoHS-compliant	Yes

Connection



Dimensional drawing



Extract accessories program

VK000041



Adaption, M12 Female (socket)
4pin Straight, M8 Male
(connector) 4pin Straight, 24V, -
25-85°C, IP67, Oil and cooling
lubricants, Welding area

VK030F80



Connection cable, 0.3m, M8
socket 3-pin angular, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK030F84



Connection cable, 0.3m, M8
socket 3-pin straight, M12
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK200021



Connection cable, 2m, M12
Female (socket) 3pin Angular, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 250V, -
30-90°C, IP67, Suitable for trailing
chain and torsion resistant, Oil and
cooling lubricants, Welding area,
Silicone-free

VK200025



Connection cable, 2m, M12
Female (socket) 3pin Straight, Free
conductor end, 3x0.34mm², PUR
(Polyurethane), Ø4.3mm, 250V, -
30-90°C, IP67, Suitable for trailing
chain and torsion resistant, Oil and
cooling lubricants, Welding area,
Silicone-free

VK030F60



Connection cable, 0.3m, M12
socket 3-pin angular, M8
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK030F64



Connection cable, 0.3m, M12
socket 3-pin straight, M8
connector 3-pin straight, 3x0.
34mm², PUR (polyurethane), 60V,
IP67, suitable for trailing chain and
torsion resistant, oils and cooling
lubricants, welding area, silicone-
free

VK030F21



Connection cable, 0.3m, M12
socket 4-pin angular, M12
connector 4-pin straight, 4x0.
34mm², 240V, IP67, suitable for
trailing chain and torsion resistant,
oils and cooling lubricants,
welding area, silicone-free

VK030F25



Connection cable, 0.3m, M12
socket 4-pin straight, M12
connector 4-pin straight, 4x0.
34mm², PUR (polyurethane),
240V, IP67, suitable for trailing
chain and torsion resistant, oils
and cooling lubricants, welding
area, silicone-free

You can find further accessories on our homepage



Installation

Mounting / installation may only be carried out by a qualified electrician!



Disposal

WEEE number according to § 6 para. 3
ElektroG: 40951076

Safety warnings

/ Before initial operation, please make sure to follow all safety instructions that may be provided in the product information.

/ Never use these devices in applications where the safety of a person depends on their functionality.